



**Application Part Number:** SL00207 (Rear Kit)



**Developed On:** 2019 Civic Si Coupe FWD



**Recommended Ride Pressure:** 36 PSI  
*(Do not exceed 200 PSI)*



**Recommended Damping:** 5 Clicks  
*(Clockwise clicks from full soft)*



**Recommended Thread Length:** 130 mm  
*(Measurement between lockrings)*



**Developed On:** 2019 Honda Civic Sedan FWD



**Recommended Ride Pressure:** 42 PSI  
*(Do not exceed 200 PSI)*



**Recommended Damping:** 5 Clicks  
*(Clockwise clicks from full soft)*



**Recommended Thread Length:** 130 mm  
*(Measurement between lockrings)*



**Developed On:** 2018 Honda Accord FWD



**Recommended Ride Pressure:** 45 PSI  
*(Do not exceed 200 PSI)*



**Recommended Damping:** 5 Clicks  
*(Clockwise clicks from full soft)*



**Recommended Thread Length:** 130 mm  
*(Measurement between lockrings)*

## Installation Notes:

Inflate air spring and align upper mount before setting the car on the ground.

**NOTE:** The recommendations and notes in this document were derived from the research and road testing conducted by Bag Riders using the vehicle listed above. If you are installing part(s) on a different vehicle, please ensure that air spring clearances are checked throughout the entire suspension travel range, including fully collapsed (aired out). In regards to damping and pressure recommendations: these are what we preferred for ourselves. We encourage you to experiment and find your most ideal suspension feel on your personal vehicle. Use our recommendations as a starting point!